

Application No. 10/735,433  
Filing Date 12/12/2003

Docket JP920030163US1

### IN THE CLAIMS

Please amend the claims as follows:

1. (currently amended) A method for accessing resources within a data processing network, comprising the steps of:

computing a set of hash values representing a set of resources stored in association with at least one data processing system within the network;

storing the computed set of hash values;

in response to a requirement for access to a first resource which is accessible via a bandwidth-sensitive connection, retrieving a hash value derived from the required first resource;

comparing the retrieved hash value with the stored set of hash values to identify a match between the retrieved hash value and any of the stored set of hash values;

in response to identifying a match for the retrieved hash value, initiating retrieval of the required first resource from said at least one data processing system; and, ~~if no match is identified for the retrieved hash value, retrieving the required first resource via said bandwidth-sensitive connection, including initiating retrieval of the required first resource via said bandwidth-sensitive connection in parallel with initiating retrieval of the required first resource from said at least one data processing system.~~

2. (original) The method of claim 1, wherein the step of retrieving the hash value derived from the required first resource comprises:

sending a resource access request to a server computer via the bandwidth-sensitive connection; and

receiving the hash value from the server computer via the bandwidth-sensitive connection.

3-4. (canceled)

Application No. 10/735,433  
Filing Date 12/12/2003

Docket JP920030163US1

5. (currently amended) The method of claim 3, wherein the required first resource has bits arranged in a sequence, and the step of initiating retrieval of the required first resource from said at least one data processing system comprises:

~~\_\_\_\_\_ initiating retrieval of resource size information and~~ initiating retrieval of the bit sequence of said required first resource in a reverse order relative to the retrieval of said required first resource via the bandwidth-sensitive connection; and wherein the method includes:

~~\_\_\_\_\_ combining portions of the bit sequence of said required first resource received via the bandwidth-sensitive connection and received from said at least one data processing system to build the bit sequence of said required first resource.~~

6. (currently amended) A method for accessing resources within a data processing network, comprising the steps of:

computing a set of hash values representing a set of resources distributed across a plurality of data processing systems within a local area network (LAN), the resources within said set of resources being accessible from respective ones of the plurality of data processing systems;

storing the set of hash values together with an identification of a respective data processing system of said plurality of data processing systems storing the resource corresponding to each of the set of hash values;

in response to a requirement for access to a resource which is stored at a remote data processing system, retrieving from the remote data processing system a hash value derived from the required resource;

comparing the retrieved hash value with the stored set of hash values to identify a match between the retrieved hash value and any of the stored set of hash values;

in response to identifying a match for the retrieved hash value, initiating retrieval of the required resource from a respective one of the plurality of data processing systems at which the resource corresponding to the matched hash value is stored; and, ~~if no match is identified for the retrieved hash value, retrieving the required resource from said remote data processing system, including initiating retrieval of the required resource from~~

Application No. 10/735,433  
Filing Date 12/12/2003

Docket JP920030163US1

the remote data processing system in parallel with initiating retrieval of the required resource from the one of the plurality of data processing systems at which the resource corresponding to the matched hash value is stored.

7. (original) The method of claim 6, wherein the set of hash values and identification of a respective data processing system are stored with information regarding the location within storage of the respective data processing system of the resource corresponding to the hash value.

8-18. (canceled)

19. (withdrawn) A method for accessing resources within a data processing network, comprising the steps of: computing a hash value representing a resource stored at a server data processing system; and embedding the hash value within a hyperlink of a data entity associated with the resource.

20. (withdrawn) The method of claim 19, further comprising: embedding at least one additional resource reference within the hyperlink, to generate a hyperlink that comprises a plurality of resource references.

21. (withdrawn) The method of claim 20, further comprising: embedding within the hyperlink relative priorities associated with each of the plurality of resource references.

22. (withdrawn) The method of claim 19, wherein the steps of computing a hash value and embedding the hash value in a hyperlink are performed in response to a request for access to the data entity.

23. (withdrawn) The method of claim 19, wherein the steps of computing a hash value and embedding the hash value in a hyperlink are performed by a preprocessor which scans data entities for hyperlinks, determines the hash value of a resource

Application No. 10/735,433  
Filing Date 12/12/2003

Docket JP920030163US1

referenced by the hyperlink, and embeds the determined hash value within the hyperlink.

24. (withdrawn) A method for accessing resources within a data processing network, comprising the steps of: storing a set of hash values computed from a set of resources, wherein the resources are available from at least one data processing system within the network; receiving a hash value representing a desired resource, and comparing the received hash value with the stored set of hash values to identify a match between the received hash value and any of the stored hash values; and in response to identifying a match for the received hash value, initiating retrieval of the required resource from said at least one data processing system.

25. (withdrawn) The method of claim 24, further comprising: in response to failure to identify a match for the received hash value by comparison with the set of hash values, initiating a communication with a data processing apparatus storing a second set of hash values and initiating a comparison between the received hash value and the hash values of the second set of hash values.

26. (withdrawn) A method for accessing resources within a data processing network, comprising the steps of: receiving a data entity including a hyperlink that references a server computer and references a resource by means of a hash value representing the resource; in response to user selection of the hyperlink, sending a resource-access request including the hash value to the referenced server computer.

27. (withdrawn) The method of claim 26, further comprising the steps of: for a received data entity including a hyperlink that comprises a plurality of resource references and associated relative priorities of each of the plurality of resource references, determining the resource reference having the highest priority, identifying a server computer from the highest priority resource reference, and sending to the identified server computer a resource-access request including the highest priority resource reference.

Application No. 10/735,433  
Filing Date 12/12/2003

Docket JP920030163US1

28. (withdrawn) The method of claim 27, further comprising the steps of: in response to a notification that the resource identified by the highest priority resource reference is inaccessible via the server computer, determining the resource reference having the second highest priority, identifying a respective server computer from the second highest resource reference, and sending to the respective identified server computer a resource-access request including the second highest resource reference.

29. (withdrawn) A method for computing an identifier for a resource, comprising the steps of: scanning the resource to identify hash-based URIs within hyperlinks embedded in the resource; extracting the hash-based URIs from the hyperlinks to generate a modified resource which does not contain the extracted hashes; and applying a secure hash function to the modified resource to compute a hash value representing the modified resource.

30-32. (canceled)

33. (new) The method of claim 5, including the steps of:  
retrieving information indicating size of the first required; and  
completing the combining responsive to a total number of bits retrieved reaching the indicated size of the first required resource.

34. (new) The method of claim 6, wherein the required first resource has bits arranged in a sequence, and the step of initiating retrieval of the required first resource from said at least one data processing system comprises:

initiating retrieval of the bit sequence of said required first resource in a reverse order relative to the retrieval of said required first resource via the bandwidth-sensitive connection; and wherein the method includes:

combining portions of the bit sequence of said required first resource received via the bandwidth-sensitive connection and received from said at least one data processing system to build the bit sequence of said required first resource.

Application No. 10/735,433  
Filing Date 12/12/2003

Docket JP920030163US1

35. (new) The method of claim 34, including the steps of:  
retrieving information indicating size of the first required resource for use in  
controlling the combining; and  
completing the combining responsive to a total number of bits retrieved reaching  
the indicated size of the first required resource.

36. (new) A computer program product, stored on a tangible, computer readable  
medium, for accessing resources within a data processing network, the data processing  
network including a local area network ("LAN") and a remote network outside the LAN,  
said computer program product having instructions for execution by a computer, wherein  
the instructions when executed by the computer, cause the computer to implement a  
method comprising the steps of:

storing a set of hash values representing a set of resources, the resources being  
stored within the LAN;

in response to a requirement for access to a first resource accessible via the remote  
network, retrieving a hash value derived from the required first resource;

comparing the retrieved hash value with the stored set of hash values to identify a  
match between the retrieved hash value and any of the stored set of hash values;

in response to identifying such a match, initiating retrieval of the required first  
resource from said LAN and from said remote network, including initiating retrieval of  
the required first resource from said LAN in parallel with initiating retrieval of the  
required first resource from said remote network.

37. (new) The computer program product of claim 36, wherein the step of  
retrieving the hash value derived from the required first resource comprises:

sending a resource access request to a server computer at the remote network; and  
receiving the hash value from the server computer.

Application No. 10/735,433  
Filing Date 12/12/2003

Docket JP920030163US1

38. (new) The computer program product of claim 36, wherein the required first resource has bits arranged in a sequence, and the step of initiating retrieval of the required first resource comprises:

initiating retrieval of the bit sequence of said required first resource from the LAN in a reverse order relative to the retrieval of said required first resource from the remote network; and wherein the instructions when executed by the computer, cause the computer to implement the method such that the method further comprises the steps of:

combining a portion of the bit sequence of said required first resource received from the LAN and a portion of the bit sequence of said required first resource received from the remote network to build a complete bit sequence of said required first resource.

39. (new) The computer program product of claim 38, wherein the instructions when executed by the computer, cause the computer to implement the method such that the method further comprises the steps of:

retrieving information indicating size of the first required resource; and

completing the combining responsive to a total number of bits retrieved reaching the indicated size of the first required resource.

40. (new) A computer system comprising:

a processor; and

a storage device connected to the processor, wherein the storage device has stored thereon a program for accessing resources within a data processing network, the data processing network including a local area network ("LAN") and a remote network outside the LAN, and wherein the processor is operative with the program to execute the program for performing the steps of:

storing a set of hash values representing a set of resources, the resources being stored within the LAN;

in response to a requirement for access to a first resource accessible via the remote network, retrieving a hash value derived from the required first resource;

Application No. 10/735,433  
Filing Date 12/12/2003

Docket JP920030163US1

comparing the retrieved hash value with the stored set of hash values to identify a match between the retrieved hash value and any of the stored set of hash values;

in response to identifying such a match, initiating retrieval of the required first resource from said LAN and from said remote network, including initiating retrieval of the required first resource from said LAN in parallel with initiating retrieval of the required first resource from said remote network.

41. (new) The computer system of claim 40, wherein the step of retrieving the hash value derived from the required first resource comprises:

sending a resource access request to a server computer at the remote network; and  
receiving the hash value from the server computer.

42. (new) The computer system of claim 40, wherein the required first resource has bits arranged in a sequence, and the step of initiating retrieval of the required first resource comprises:

initiating retrieval of the bit sequence of said required first resource from the LAN in a reverse order relative to the retrieval of said required first resource from the remote network; and wherein the processor is operative with the program to execute the program for further performing the steps of:

combining a portion of the bit sequence of said required first resource received from the LAN and a portion of the bit sequence of said required first resource received from the remote network to build a complete bit sequence of said required first resource.

43. (new) The computer system of claim 42, wherein the processor is operative with the program to execute the program for further performing the steps of:

retrieving information indicating size of the first required resource; and  
completing the combining responsive to a total number of bits retrieved reaching the indicated size of the first required resource.